



# Fischer Panda®

Power  
wherever  
you are™

## Panda PMS 4800i – Variable Speed



Engine Type	Farymann 18W430
Cylinder	1
Bore / stroke	82 / 55mm
Displacement	290 cm <sup>3</sup>
Start system	Electric – 12v
Cooling system	Fresh water cooled via built in heat exchanger

Alternator Type	Fischer Panda - Permanent Magnet
Voltage / Frequency	230v / 50Hz pure sine wave
Nominal Output	4.5kva / 3.8 kW
Regulation	Electronic – variable speed

Dimensions of Generator: L580mm x W370mm x H545mm,

Weight: 80kg

Weight of PMGi Inverter: 10kg

The complete generator is mounted inside a super-silent capsule type GRP – 3 DS. Fitted to the generator as standard is an engine driven water cooling pump, a built in heat exchanger for the freshwater cooling of the engine.

The output of the generator is pure sine wave 230v / 50Hz, this makes the generator very strong for starting inductive loads such as air conditioning, de-salination or even dive compressors. The output is also variable speed, the engine rpm will increase or decrease inline with the load within preset parameters, this ensures the generator is as quiet as possible and more fuel efficient.

Supplied with the generator would be fuel pump, connecting looms, full instruction manual, and new digital remote control panel giving on/off, start/stop, pre-heat, digital hour meter and all warning indications. The warning indications work on an emergency shut down principle.

Fischer Panda UK Ltd. 17 Blackmoor Road,  
Ebblake Industrial Estate, Verwood. Dorset BH31 6AX  
Tel: +44 (0)1202 820840 Fax: +44 (0)1202 828688  
[www.fischerpanda.co.uk](http://www.fischerpanda.co.uk)